

SUPERIOR[®]

Superior Battery Manufacturing Company Inc.

2016

BATTERY SPECIFICATIONS



BCI GROUP NO.	SBM PART NO.	NOTES (Page 4)	CCA @ 0 F	CA @ 32 F	RESERVE CAPACITY @ 25 AMP	Approx. WEIGHT	PALLET QTY	LENGTH inches / mm	WIDTH inches / mm	HEIGHT inches / mm			
SUPERIOR[®] 12 VOLT AUTOMOTIVE BATTERIES - MAINTENANCE FREE WITH PFX[®] TECHNOLOGY													
22F	22F18	A,C	350	435	60	28	78	9 3/8	238	6 3/4	171	8 3/16	208
24	2418	A,C,F,H	400	500	60	32	72	10 1/8	258	6 3/4	170	9	229
	2421	A,C,F,H	525	650	90	36	72	10 1/8	258	6 3/4	170	9	229
	2423	A,C,F,H	650	810	105	38	72	10 1/8	258	6 3/4	170	9	229
	2425	A,C,F,H	725	900	120	40	72	10 1/8	258	6 3/4	170	9	229
24R	24R18	A,C,F,H	400	500	60	32	72	10 1/8	258	6 3/4	170	9	229
	24R21	A,C,F,H	525	650	90	36	72	10 1/8	258	6 3/4	170	9	229
	24R23	A,C,F,H	650	810	105	38	72	10 1/8	258	6 3/4	170	9	229
	24R25	A,C,F,H	725	900	120	40	72	10 1/8	258	6 3/4	170	9	229
25	2520	A,C,F,H	550	685	90	32	78	9	229	6 5/8	169	8 3/4	222
26	2620	A,C,F,H	400	500	70	26	90	8 1/8	206	6 3/4	171	8 3/16	208
	2622	A,C,F,H	500	625	85	28	90	8 1/8	206	6 3/4	171	8 3/16	208
26R	26R20	A,C,F,H	400	500	70	26	90	8 1/8	206	6 3/4	171	8 3/16	208
	26R22	A,C,F,H	500	625	85	28	90	8 1/8	206	6 3/4	171	8 3/16	208
27	2722	A,C	550	680	90	40	54	12	305	6 1/2	167	9	229
	2724	A,C	700	875	120	44	54	12	305	6 1/2	167	9	229
27R	27R24	A,C	700	875	120	44	54	12	305	6 1/2	167	9	229
34	3423	A,C,F,H	535	665	100	34	72	10 1/8	258	6 3/4	171	8 1/16	205
	3425	A,C,F,H	650	810	115	36	72	10 1/8	258	6 3/4	171	8 1/16	205
34R	34R25	A,C,F,H	650	810	115	36	72	10 1/8	258	6 3/4	171	8 1/16	205
35	3520	A,C,F,H	550	685	90	32	78	9	229	6 5/8	169	8 3/4	222
36R	36R26	A,C	650	810	128	38	72	10 1/4	260	7 1/8	181	7 3/4	197
51	5125	A,C,F,H	500	625	80	28	96	9 5/16	236	5 1/16	128	8 13/16	224
51R	51R25	A,C,F,H	500	625	80	28	96	9 5/16	236	5 1/16	128	8 13/16	224
58	5822	A,C	450	565	70	28	72	9 1/4	235	7 1/8	181	7	178
	5825	A,C	550	685	90	31	72	9 1/4	235	7 1/8	181	7	178
58R	58R25	A,C	550	685	90	31	72	9 1/4	235	7 1/8	181	7	178
62	6223	A,C	525	650	90	35	78	8 3/4	222	6 1/4	159	8 7/8	226
65	6526	A,C,H	650	810	120	40	54	12 1/8	308	7 7/16	188	7 5/8	193
	6529	A,C,H	825	1030	150	42	54	12 1/8	308	7 7/16	188	7 5/8	193
70	7020	C,F,H,S	400	500	70	29	90	8 1/8	206	7 1/8	181	7 3/16	182
	7022	C,F,H,S	500	625	85	31	90	8 1/8	206	7 1/8	181	7 3/16	182
75	7522	C,F,H,S	500	625	85	31	75	9	229	7 1/16	180	7 3/16	182
	7525	C,F,H,S	650	810	110	35	75	9	229	7 1/16	180	7 3/16	182
78	7824	C,F,H,S	600	750	100	34	72	10 3/16	259	7 1/16	180	7 3/16	182
	7827	C,F,H,S	750	935	130	39	72	10 3/16	259	7 1/16	180	7 3/16	182
86	8622	A,C,F,H	500	625	80	31	75	8 7/8	226	6 3/4	171	8	204
96R	96R25	A,C	575	720	95	32	72	9 3/4	243	6 7/8	175	6 7/8	175
121R	121R22	A,C,F,H	550	685	85	30	90	8 1/8	206	6 7/8	175	8 1/8	206
124R	124R25	A,C,F,H	650	810	110	40	72	10 1/8	258	6 7/8	175	8 3/8	214



BATTERY SPECIFICATIONS

2515 Ky. 910, Russell Springs, KY 42642
1-800-322-6056 www.superiorbattery.com

BCI GROUP NO.	DIN Code	EN Code	SBM PART NO.	NOTES (Page 4)	CCA @ 0 F	CA @ 32 F	RESERVE CAPACITY @ 25 AMP	Approx. WEIGHT	PALLET QTY	LENGTH inches / mm	WIDTH inches / mm	HEIGHT inches / mm			
SUPERIOR® 12 VOLT EN/DIN BATTERIES - MAINTENANCE FREE WITH PFX® TECHNOLOGY															
40R	T6	66LB	40R27	A,C,H	675	845	115	37	63	10 15/16	276	6 7/8	175	7	177
42	T5	45LB	4222	A,C,H	415	515	65	29	72	9 3/8	237	6 7/8	175	6 3/4	173
47	H5	55L2	4722	A,C,H	550	685	85	31	72	9 3/4	247	6 7/8	175	7 1/16	187
48	H6	66L3	4825	A,C,H	650	810	110	38	63	10 15/16	277	6 7/8	175	7 7/16	193
	H6	66L3	4828	A,C,H	730	915	130	39	63	10 15/16	277	6 7/8	175	7 7/16	193
49	H8	LN5	4932	A,C,H	900	1125	160	51	54	13 15/16	354	6 7/8	175	7 7/16	193
90	T5	45LB	9025	A,C	550	685	90	33	72	9 9/16	243	6 7/8	175	6 7/8	175
91	T6	66LB	9128	A,C,H	650	810	100	37	63	10 15/16	277	6 7/8	175	7	178
94R	H7	77L4	94R28	A,C,H	740	915	135	41	54	12 5/16	313	6 7/8	175	7 7/16	193

BCI GROUP NO.	SBM PART NO.	NOTES (Page 4)	CCA @ 0 F	CA @ 32 F	RESERVE CAPACITY @ 25 AMP	Approx. WEIGHT	PALLET QTY	LENGTH inches / mm	WIDTH inches / mm	HEIGHT inches / mm			
SUPERIOR® 12 VOLT DUAL TERMINAL / UNIVERSAL BATTERIES - MAINTENANCE FREE WITH PFX® TECHNOLOGY													
UNIVERSAL	70T20	A,C,F,H,S	400	500	70	29	90	8 1/8	206	7 1/8	181	8 3/16	208
	70T22	A,C,F,H,S	500	625	85	31	90	8 1/8	206	7 1/8	181	8 3/16	208
	75T25	A,C,F,H,S	650	810	110	35	75	9	229	7 1/16	180	8 1/4	210
	78T24	A,C,F,H,S	600	750	100	34	72	10 3/16	259	7 1/16	180	8 3/16	208
	78T27	A,C,F,H,S	750	935	130	39	72	10 3/16	259	7 1/16	180	8 3/16	208

SUPERIOR® 12 VOLT COMMERCIAL BATTERIES - MAINTENANCE FREE WITH PFX® TECHNOLOGY													
30H	30H25	A,C	725	900	150	52	54	12 7/8	328	6 3/4	171	9 1/2	241

GROUP 31 HEAVY DUTY SERIES – MAINTENANCE FREE WITH PFX® TECHNOLOGY														
(Automotive Post)	31 A	HDA23	A,C,F,H	650	790	140	49	54	12 7/8	328	6 3/4	171	9 5/16	237
		HDA25	A,C,F,H	725	900	170	52	54	12 7/8	328	6 3/4	171	9 5/16	237
		HDA29	A,C,F,H	925	1150	200	57	54	12 7/8	328	6 3/4	171	9 5/16	237
		HDA31	A,C,F,H	1000	1250	205	60	54	12 7/8	328	6 3/4	171	9 5/16	237
(Threaded Post)	31 T	HD23	C,F,H,T	650	790	140	49	54	12 7/8	328	6 3/4	171	9 5/16	237
		HD25	C,F,H,T	725	900	170	52	54	12 7/8	328	6 3/4	171	9 5/16	237
		HD29	C,F,H,T	925	1150	200	57	54	12 7/8	328	6 3/4	171	9 5/16	237
		HD31	C,F,H,T	1000	1250	205	60	54	12 7/8	328	6 3/4	171	9 5/16	237

GROUP 31 SEVERE DUTY SERIES – MAINTENANCE FREE WITH PFX® TECHNOLOGY													
31 A	SDA25	A,C,F,H,P,X	730	910	190	57	54	12 7/8	328	6 3/4	171	9 5/16	237
	SDA29	A,C,F,H,P,X	940	1175	220	66	54	12 7/8	328	6 3/4	171	9 5/16	237
31 T	SD25	C,F,H,P,T,X	730	910	190	57	54	12 7/8	328	6 3/4	171	9 5/16	237
	SD29	C,F,H,P,T,X	940	1175	220	66	54	12 7/8	328	6 3/4	171	9 5/16	237

BCI GROUP NO.	SBM PART NO.	NOTES (Page 4)	CCA @ 0 F	CA @ 32 F	RESERVE CAPACITY @ 25 AMP	Approx. WEIGHT	PALLET QTY	LENGTH inches / mm	WIDTH inches / mm	HEIGHT inches / mm			
12 VOLT COMMERCIAL BATTERIES													
4D	4D31	A,H,Y	920	1150	225	96	30	20 3/4	527	8 11/16	220	10	255
	4D35	A,H,Y	1080	1350	300	99	30	20 3/4	527	8 11/16	220	10	255
	4DHC	A,G,H,Y	1300	1625	375	107	30	20 3/4	527	8 11/16	220	10	255
4DLT	4DLT	A,Y	900	1125	200	81	30	19 7/8	505	8 3/16	208	8 1/4	209

BCI GROUP NO.	SBM PART NO.	NOTES (Page 4)	CCA @ 0 F	CA @ 32 F	RESERVE CAPACITY @ 25 AMP	Approx. WEIGHT	PALLET QTY	LENGTH inches / mm	WIDTH inches / mm	HEIGHT inches / mm			
12 VOLT COMMERCIAL BATTERIES (cont.)													
8D	8D37	A,H,Y	1100	1375	320	112	24	20 3/4	527	10 7/8	277	10	255
	8D45	A,H,Y	1300	1625	400	123	24	20 3/4	527	10 7/8	277	10	255
	8D47	A,H,Y	1400	1750	435	126	24	20 3/4	527	10 7/8	277	10	255
	8DHC	A,G,H,Y	1400	1750	450	126	24	20 3/4	527	10 7/8	277	10	255
6 VOLT COMMERCIAL BATTERIES													
1	GP125	A,C	700	875	150	31	72	8 15/16	227	6 3/4	171	8 3/4	222
4	GP433	A,C	1000	1250	240	47	54	12 7/16	316	6 3/16	157	9 3/8	238
6 VOLT GOLF CAR BATTERIES													
GC2	GC61200	G,L	210	105	400	60	48	10 1/4	260	7 1/8	181	11 1/8	284
	GC61300	G,L	225	115	450	65	48	10 1/4	260	7 1/8	181	11 1/8	284
8 VOLT GOLF CAR BATTERIES													
	GC81200	G,L	170	120	300	63	48	10 1/4	260	7 1/8	181	11 1/8	284
12 VOLT LAWN AND GARDEN BATTERIES - MAINTENANCE FREE WITH PFX® TECHNOLOGY													
U1	U1LS4	C,F	245	305	25	16	160	7 3/4	197	5 1/8	130	7 5/16	186
	U1LS6	C,F	300	375	35	17	160	7 3/4	197	5 1/8	130	7 5/16	186
U1R	U1RS4	C,F	245	305	25	16	160	7 3/4	197	5 1/8	130	7 5/16	186
	U1RS6	C,F	300	375	35	17	160	7 3/4	197	5 1/8	130	7 5/16	186
SUPERIOR® 12 VOLT STARTING MARINE BATTERIES - MAINTENANCE FREE WITH PFX® TECHNOLOGY													
24M	M2418	C,F,H,M	400	500	70/60	33	72	10 1/8	258	6 3/4	170	9 1/8	231
	M2421	C,F,H,M	525	650	100/90	37	72	10 1/8	258	6 3/4	170	9 1/8	231
	M2427	C,F,H,M	800	1000	145/130	41	72	10 1/8	258	6 3/4	170	9 1/8	231
27M	M2727	C,H,M	800	1000	205/180	54	54	12 3/8	320	6 11/16	170	9 1/4	235
SUPERIOR® 12 VOLT MARINE-RV/DUAL PURPOSE BATTERIES - MAINTENANCE FREE WITH PFX™ TECHNOLOGY													
24M	24DP19	C,H,M,X	450	595	105/95	37	72	10 11/16	272	6 5/8	168	9 1/4	235
27M	27DP23	C,H,M,X	625	780	175/155	47	54	12 5/8	320	6 5/8	168	9 1/4	235
SUPERIOR® 12 VOLT MARINE-RV/DEEP CYCLE BATTERIES													
24M	24DC21	C,H,M,X	525	655	130/120	40	72	10 11/16	272	6 5/8	168	9 1/4	235
27M	27DC25	C,H,M,X	700	860	200/180	50	54	12 5/8	320	6 5/8	168	9 1/4	235
31M	31DC29	C,F,H,M,X	885	1100	250/225	59	54	12 7/8	328	6 3/4	171	9 5/16	237



Notes:
A - SAE Post
C - Calcium Construction
F - Flat Cover Design
G - Glass Mat
H - Handle(s)
L - LPT Post

M - Marine TwinPost
P - Plate Bonding (GridLoc Tech)
S - Side Terminal
T - Threaded Post
X - Embedded Glass Mat
Y - Hybrid Construction
www.superflex.com

